

Data sheet

Vantageo 2240-RS

Flexible, Scalable, and Secure



2U Hyper with 12 hot-swap 3.5" NVMe/SAS/SATA bays and 4 PCle 5.0 ×16 slots + up to 2 PCle 5.0 ×16 AlOM slots

Key Applications

- 1. Virtualization
- 2. Al Inference and Machine Learning
- 3. Enterprise Server
- 4. Software-defined Storage
- 5. Cloud Computing

Key Features

- 1. Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors
- 2. 32 DIMM slots supporting up to 8TB of memory; RDIMMs up to DDR5-5600
- 3. Optional PCIe slot configurations up to 8 PCIe 5.0 x8 or 4 PCIe 5.0 x16 slots with support for double-width GPU/Accelerator cards
- 4. Flexible networking options with up to 2 AIOM networking slots (OCP NIC 3.0 compatible)
- 5. 4 heavy duty hot-swap fans with optimal fan speed control

Vantageo 2240-RS	
Features	Technical Specification
Processor	Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors
Chip Set	Intel® C741
Memory	Slot Count: 32 DIMM slots Max Memory (1DPC): Up to 4TB 5600MT/s ECC DDR5 RDIMM Max Memory (2DPC): Up to 8TB 4400MT/s ECC DDR5 RDIMM
Drive bays	Default: Total 12 bay(s) 12 front hot-swap 3.5" NVMe*/SAS*/SATA* drive bay(s)
Power supplies	2x 1200W Redundant Titanium Level power supplies
Dimensions	Height: 40 mm Width: 73.5 mm Length: 265 mm(max.) *Dimensions do not include bezel
Embedded management	Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
GPU	Max GPU Count Up to 1 double-width GPU(s) Supported GPU NVIDIA PCIe: H100, L40S, A40, A100
Security	Trusted Platform Module (TPM) 2.0 Silicon Root of Trust (RoT) – NIST 800-193 Compliant
I/O & Ports	LAN 1 RJ45 1 GbE Dedicated BMC LAN port(s) USB 2 USB 2.0 port(s) (2 rear) Video 1 VGA port(s)
Supported operating systems	Win server 2022/2019 RHEL/Ubuntu/Centos Windows® 11, Windows® 10 64-bit
operating Environment	Operating Temp. $10^{\circ}\text{C} \sim 35^{\circ}\text{C}$ (50°F $\sim 95^{\circ}\text{F}$) Non Operating Temp. -40°C to 70°C (- 40°F to 158°F)
Recommended support	 24x7 - 4 hours Response, Next Business Day Call to Resolution CTR 24x7 - 4 hours Response, 24 Hours Call to Resolution CTR 24x7 - 4 Hours Response, 6 Hours Call to Resolution CTR Default support Next Business Day Consulting and deployment offerings are also available. Contact Vantageo representative for the more information.